

TP-135

Compact Portable Two-Way Radio

TalkPod[™] TP-135 is an value personalized handheld commercial two-way radio. With simple, stylish appearance and clear sound, this two-way radio is the best choice for small hotel services, entertainment establishments, supermarkets and shopping malls and other commercial areas.

Excellent Automatic Battery Save Mode Personalized Colorful Shell Reliable and Economic Unique Audio Chamber Design Clear and High Audio Quality CTCSS / DCS

Personalized Colorful Shell

TP-135 has blue, yellow, green, gray, red five colorful series for your free selecting, which can release your personality and hobbies.

Reliable and Economic

TP-135 has simple and stylish appearance and clear sound which can bring you reliable, economic experience.

Unique Audio Chamber Design

Unique sound chamber design, exclude the interference of the environment, and allows users to send and receive more accurate and clear information.

Clear and High Audio Quality

Using advanced audio chamber control system and encryption of CDCSS and Analog CTCSS, users can receive information more clearly.

Voice Over

TP-135 can broadcast the current channel number, letting you know on which channel your radio is operating. Also, the local language can be downloaded into TP-135 for broadcast as per users' needs.

Unique Audio Chamber Design

Unique sound chamber design exclude the interference of the environment, and allows users to send and receive information more accurately and clearly.

Voice Operated Transmit (VOX)

Enjoy the convenience of hands-free operation when used with optional accessories.

Time-out Timer

The feature allows for more efficient use of channels by limiting the amount of time of each transmission.

Monitor

Allows users to monitor the activity on the current channel. The feature is especially helpful for receiving a weak signal.

Low Battery Alert

Alert users to recharge the battery should the battery level run





General Specifications

General Specifications	
Model Number	TP-135
Frequency Range	UHF 400-470MHz
Channel Capacity	16
Channel Spacing	25 /20/12.5KHz
Operating Voltage	3.7V DC
Battery	1600mAh Li-Ion Battery
Battery Life (5-5-90 Duty Cycle)	12 hours
Frequency Stability	±2.5 ppm
Operating Temperature	-25℃~+65℃
Antenna Impedance	50Ω
Dimensions (H×W×D) (with battery, without antenna)	115mm×55mm×31mm
Weight (with antenna & battery)	176.8g
Transmitter	
RF Power Output	1 to 4W
Modulation	F3E
Spurious and Harmonics	-
FM Noise	-
Current consumption	≤1.5A
Audio Distortion	≥10%
Receiver	
Sensitivity	0.2μV
Selectivity	60dB
Intermodulation	60dB
Spurious Response Rejection	60dB
Rated Audio Power Output	≥0.5W
Rated Audio Distortion	≥10%

^{*} Specifications subject to change without notice.











Quanshun Communication Technology Co. Ltd

Quanshun Bldg., Daxiamei, Nan'an, Quanzhou, Fujian, China 362302 Tel: (86 595) 8675 3355 / 8675 5555 Fax: (86 595) 8675 8299