

TP-625

Professional Portable Two-Way Radio

TalkPodTM TP-625 is a high-quality, high-power commercial handheld two-way radio. Due to its advanced signaling encryption, automatic eliminating ambient noise, and FM radio broadcast, it improves the user's communications experience to a whole new level.

Compact and Durable Body
Superior, Stylish and Eye-catching Appearance
Unique Audio Chamber Design
Super Penetrability
Filtering Ambient Noise
High-Quality Sound Against The Tumult

Compact and Durable Body

Made of pure CP raw materials, TP-625 has compact structure and can stand abrasion and drop.

Voice Over

TP-625 can broadcast the current channel number, letting you know on which channel your radio is operating. Also, the local language can be downloaded into TP-625 for broadcast as per users' needs.

Superior, Stylish and Eye-catching Appearance

With human-computer interaction design concept, its superior, stylish and eye-catching appearance make people too hard to put it down.

Unique Audio Chamber Design

Unique sound chamber design exclude the interference of the environment, and allows users to send and receive information more accurately and clearly.

Super Penetrability

A powerful speaker ensures clear, crisp and strong penetrability, even in noisy environments. Even if you are in lift, basement or building, the TP-625 will bring you prompt and reliable communication.

High-Quality Sound Against The Tumult

In a noisy environment, the Two-way radio can automatically adjust to filter the ambient noise, and allows users to receive high-definition signal.

Busy Channel Lockout

Avoid interference with the users using the same channel by preventing transmission if another talk group is already on the air.

Voice Operated Transmit (VOX)

Enjoy the convenience of hands-free operation when used with optional accessories.

Time-out Timer

The feature allows for more efficient use of channels by limiting the amount of time of each transmission.

Monitor

Allows users to monitor the activity on the current channel. The feature is especially helpful for receiving a weak signal.

Low Battery Alert

Alert users to recharge the battery should the battery level run





General Specifications

General Specifications	
Model Number	TP-625
Frequency Range	VHF 136-174MHz / UHF 400-470MHz
Channel Capacity	16
Channel Spacing	25 /20/12.5KHz
Operating Voltage	7.4V DC
Battery	2000mAh Li-Ion Battery
Battery Life (5-5-90 Duty Cycle)	16 hours
Frequency Stability	±2.5 ppm
Operating Temperature	-25℃~+65℃
Antenna Impedance	50Ω
Dimensions (H×W×D) (with battery, without antenna)	115mm×55mm×31mm
Weight (with antenna & battery)	189.1g
Transmitter	
RF Power Output	1 to 5W
Modulation	F3E
Spurious and Harmonics	-
FM Noise	-
Current consumption	≤1.5A
Audio Distortion	≥10%
Receiver	
Sensitivity	< 0.2µV
Selectivity	60dB
Intermodulation	60dB
Spurious Response Rejection	60dB
Rated Audio Power Output	≥500mW
Rated Audio Distortion	≥10%

^{*} Specifications subject to change without notice.











Quanshun Communication Technology Co. Ltd

Quanshun Bldg., Daxiamei, Nan'an, Quanzhou, Fujian, China 362302 Tel: (86 595) 8675 3355 / 8675 5555 Fax: (86 595) 8675 8299